



EG100 “Smart Alert Communicator” Two-Way Voice Station

To keep seniors well-being a top priority, Electronique Giant’s system architecture and enhanced products are made using leading edge technology.

Main Features

- Backlit emergency button..... Button illuminated in red for visibility during the night
- Escalation progress tones.... Built-in soft alert and escalation progress notification sounds
- Two-way response Hand-free intercom conversation response
- Scalable acoustics Powerful speaker & microphone half-duplex EG technology
- 10 wireless devices..... Supervised self-auto reporting smart EG201 transmitters
- Unique electronic ID..... Real time field equipment inventory management
- 3 Identification protocols..... EG Serial Number, Telco Caller ID and Ademco Contact ID
- 5 call modes..... Retirement home rooms, common area localization, remote 24/7 central agents, family personal phone numbers and dry contacts
- Data & audio reporting..... Inventory, alerts and equipment status
- Equipment status report..... Priority based communication event
- Station programming SD-Card, Pair key, Sync key and scheduled auto-programing
- Led indicators..... Visual led station DC power and live phone line led status indicators
- Station test transmitter..... Reporting silent testing EG201-Test transmitter
- Custom top cover Retirement Home design, information and 5 programmable soft keys



EG100 “Smart Alert Communicator” Two-Way Voice Station

PR500 Overview

- Browser client interface Enabled Html V5 secured application set for PCs, Smartphone sand Tablets
- Nurse Call applications..... Dashboard, escalation, unit management, reports (scheduled & custom) and alert console annunciator
- Central monitoring Central monitoring services client account management
- PABX phone system..... Client phone service management applications (packages, billing, room and administration services)
- Applications Phone based services for inactivity, medication reminder, audio message diffusion and
- Technical Support Download support files, EG100 code generator and online RMA
- Administrator Users access right management by group restriction

Monitoring Features

- EG100 inactivity
- EG100 active phone line
- EG100 DC power & low battery
- EG100 hardware, firmware and data
- Room numbers duplicates
- EG201 inactivity
- EG201 low battery
- EG201 serial number duplicates
- Alert and failure data logs

Phone Features

- Hearing aid handset compatible
- 5 custom service speed soft keys
- Flash, pause, redial and volume keys
- Incoming / outgoing call hand-free key

Power Supply

- 12V 500mA DC adaptor
- Rechargeable battery AAA NiMH 7.2V
- 28 hours back up battery standby

Unit Dimensions

- 23cm(L) x 15cm (H) x 6cm (D)
- Weight 775g

Working Environment

- Operating temperature (-20°C – 70°C)
- Humidity (0 – 95%)

Monitoring EG Infrastructure

- Remote “Cloud” data backup
- Remote “Cloud” system relay

Included in a box

- EG100 station with lifter and line cord
- Top plastic cover protector
- Top custom identification card
- AC 12V power adapter
- Handset with standard cord

Radio Frequency

- 303.875 MHz
- Superheterodyne receiver
- Open air range : 45m

Dry contact EG100 box

- Third party devices (RFID, pull cords ...)

Regulation Compliance

- FCC REN 0.3(B), Part 15 & Part 68